



NOTES:

- A. SLOPE PROTECTION SHOWN IN THIS DETAIL INCLUDES MINIMUM REQUIREMENTS.
- B. SLOPE PROTECTION SHALL BE DESIGNED FOR SITE SPECIFIC CONDITIONS BY A DESIGN PROFESSIONAL REGISTERED IN THE STATE OF WASHINGTON.
- C. JUTE/COIR FABRIC MAY BE USED IN LIEU OF WALERS AND STAKING. JUTE FABRIC AND STAKES SHALL BE 100% BIODEGRADABLE MATERIAL WITH AN 18 MONTH LIFE AND SHALL BE SECURED IN PLACE ACCORDING TO MANUFACTURER'S RECOMMENDATIONS.
- D. STRAW WATTLES MAY BE USED IF APPROVED BY THE PARK PROJECT MANAGER. STRAW WATTLES SHALL BE INSTALLED IN ACCORDANCE WITH WSDOT STANDARD PLAN I-30.30-00 AND SHALL BE MADE OF 100% BIODEGRADABLE MATERIAL WITH AN 18 MONTH LIFE.
- E. WOOD STAKES AND WALERS SHALL BE ALL NATURAL WOOD SPECIES, UNTREATED.
- F. EXTENT AND LENGTH OF WALERS SHALL BE SHOWN ON THE FINAL GRADING PLAN.
- G. IF HARD SUBGRADES ARE ENCOUNTERED, WOOD STAKES MAY NEED TO BE MECHANICALLY DRIVEN INTO THE GROUND TO ACHIEVE THE REQUIRED EMBEDMENT DEPTH.

**PARKS AND RECREATION
DESIGN AND DEVELOPMENT
JUNE 3, 2010**

**CITY OF BELLINGHAM
SLOPE PROTECTION
Scale: 1/2" = 1'-0"**

**DRAWING
2270.01**