



NOTES:

- USE OF THIS DETAIL MAY NOT BE SUITABLE FOR ALL SITES AND MUST BE PREAPPROVED BY THE PARK PROJECT MANAGER.
- PREFABRICATED STEPS PROVIDED BY PACIFIC CONCRETE INDUSTRIES, 360-734-0910 OR APPROVED EQUAL
- INSTALL STEPS LEVEL AND INCLINED AT 2% TO DRAIN IN DIRECTION OF TRAVEL.
- LIGHT BROOM OR SANDBLAST FINISH
- SEE DETAILS 03300.02, 03300.03, 03300.04 FOR STAIR DETAIL & SIDEWALL OPTIONS.
- MINIMUM/MAXIMUM TREAD DEPTH SHALL BE 12" AND 14" RESPECTIVELY. ALL TREADS SHALL BE EQUAL IN DEPTH.
- THE MAXIMUM TOTAL RISE OF STEPS SHALL BE BASED ON REQUIREMENTS OF THE PROJECT.
- LANDINGS AND INTERMEDIATE HANDRAIL SUPPORT POSTS SHALL BE BASED ON THE REQUIREMENTS OF THE PROJECT.

**PARKS AND RECREATION
DESIGN AND DEVELOPMENT
APRIL 7, 2010**

**CITY OF BELLINGHAM
PRE-FABRICATED CONCRETE
STEP & HANDRAIL**

**DRAWING
03300.01**