

DESIGN STANDARDS FOR: LOUVERS AND VENTS

Ceiling Mounted Fan Standard:

- 1. WhisperCeiling model #FV-08VQ2 90 CFM 4" duct manufactured by Panasonic.
- 2. Note: An approved equal will not be accepted. Sole source justification is based on bulk parts on hand; ease on maintenance time, availability, and vandal resistance.

WITSIEF CEILING

FV-05VQ2

60 CFM-4" Duct

FV-07VQ2

70 CFM-4" Duct



90 CFM-4" Duct FV-11VQ2

110 CFM-4" Duct

FV-11VQD2

110/60 CFM-4" Duct

Advantages:

- Super quiet operation
- ENERGY STAR® qualified
- Totally enclosed condenser motor for long life rated for continuous run
- Easy installation (double hanger bar system)
- Rust proof paint treatment on galvanized housing

Ceiling Mounted Fan



- Built-in damper to prevent backdraft
- Contemporary grille design
- UL listed for tub/shower enclosure when used with a GFCI branch circuit wire
- Thermal fuse protection
- Meets Washington State Ventilation and Indoor Air Quality Code

WhisperCelling		FV-05VQ2		FV-07VQ2		FV-08VQ2		FV-11VQ2		FV-11VQD2 2-speed			
											High		Low
Characteristics	Statistic pressure in inches w. g.	0.1	0.25	0.1	0.25	0.1	0,25	0.1	0.25	0.1	0.25	0.1	0.25
(HVI Certified Data for 0.1° S.P.)	Air Volume (CFM)	60	44	70	54	90	75	110	94	110	91	60	51
	Noise (sones)	<0.3	N/A	0.3	N/A	0.7	N/A	1.5	N/A	1.5	N/A	<0.3	N/A
	Power Consumption (Watts)	14	13	19	18	21	20	27	26	27	-25	18	17
	Energy Efficiency (CFMs/Watt)	4.3	3.4	3.7	3.1	4.3	3.8	4.4	3.6	4.1	3.6	3.3	3.0.
	ENERGY STAR Qualified	Yes		Yes		Yes		Yes		Yes			
	Duct Diameter (inches)	4		4		4		4		4			
Approved	UL Tub/Shower Enclosure	Yes		Yes		Yes		Yes		Yes			
Code/Standard/	Washington State VIAQ Code	Yes		Yes		Yes		Yes		Yes			
Regulation	Mfg in ISO 9001 Certified Facility	Yes		Yes		Yes		Yes		Yes			

Complete Specification on page 38. Performance Curve Charts on page 30.


N/A=not applicable w.g.=water gauge S.R=static pressure

#\$	Panasonic ventilation fans may qualify for an energy saving rebate.
vided b	Rebate programs are often pro- by local utility companies and based
on EN	ERGY STAR guidelines. Check with
your lo	cal utility company for details.

WhisperCeiling 2-speed FV-11VQD2

Whole-House (60 CFM) and Spot (110 CFM) ventilation combined in a 2-speed ceiling mount fan.

Dimensions



Ideal for airtight homes that require continuous or long run ventilation.

3-position switch included

18

WhisperCeiling ventilation catalog 2003

Design Standard No. 10200.00 Date: <u>August 23, 2007</u> Page 3 of 3

END OF SECTION