

- REFERENCE DRAWING 10430.03_ALT 1 FOR SIGN PANEL AND GRAPHICS.
- INSTALL SIGN PLUMB AND LEVEL. SIGN POST SHALL BE HDPE. SUBMIT COLOR SAMPLE FOR OWNER APPROVAL BEFORE ORDERING.
- C. 3IGN FOST STATEL BE TIPE. SUBMIT COLOR SAMPLE FOR COMMENTAFFROVAL BEFORE ORDERING.

 D. ALUMINUM SIGN PANEL SHALL COMPLY WITH WSDOTSS 9-28.8

 E. ALL FASTENERS SHALL BE GALVANIZED OR STAINLESS STEEL. SIGN PANEL FASTENERS SHALL COMPLY WITH WSDOTSS 9-28.11.
- FOUNDATION DESIGN IS SHOWN FOR LEVEL GROUND ONLY WITH AN ASSUMED SOIL BEARING STRENGTH OF 1500 PSF, WHICH SHALL BE BE CONFIRMED BY A PROFESSIONAL ENGINEER/GEOTECHNICAL ENGINEER BEFORE COMMENCING WORK.
- ALL WELDS SHALL BE CONTINUOUS AND ALL AROUND. GRIND SMOOTH UNLESS OTHERWISE NOTED. WELDS SHALL BE GROUND SMOOTH BEFORE POWDER COATED.
- CLEAR, WEED, GRADE, MULCH, OR SEED SURROUNDING SITE AS SPECIFIED. RESTORE DISTURBED AREA IN ACCORDANCE WITH PARK STANDARDS
- COLORS SHALL BE AS FOLLOWS:
 - MOMENT POST BASE: MATTHEWS MP#10269 AUTO BODY PAINT W/ PRIMER, SATIN FINISH, OR MATCH DRYLAC RAL #7021 DARK GRAY, EGGSHELL FINISH

 - ALUMINUM SIGN PANEL; (BODY BACK ONLY): MATHEWS #MP14185, AUTO BODY PAINT W/ PRIMER, SATIN FINISH, OR MATCH PANTONE PMS 560C DARK GREEN, EGGSHELL FINISH.

 SIGN GRAPHICS: SHALL BE PRODUCED FROM DIGITAL FILES PROVIDED BY THE OWNER AND PROVIDED TO THE CONTRACTOR FOR PRODUCTION AND ASSEMBLY, AND PLOTTED ON A TRAFFIC GRADE VINYL SELF ADHESIVE MEDIUM THAT MEETS WSDOT STANDARDS.
 - THE FINISH SHALL BE NON-REFLECTIVE.