



## **DESIGN STANDARDS FOR: EXTERIOR LIGHTING**

---

### Building Lighting Standard:

1. Wall or Ceiling mount: Herculux model #H1212FD or ED surface mount LED manufactured by Kenall [www.kenall.com](http://www.kenall.com) phone 847-360-8200
2. Doorway security lighting: OLWX1 LED 13 watt wall luminaire by Lithonia Lighting [www.lithonia.com](http://www.lithonia.com) phone 800-279-8041

### Parking Lot Site Lighting Options (final option to be approved by Parks Project Manager):

1. Gardco Gullwing GL18, LED, with round pole adapter on 5 inch diameter straight aluminum pole, 24ft 10 inches high with black finish. Top of foundation base to be 30 inches above finished grade.

Or the following:

2. Sterner Executive RT-25, LED, with 25ft pole, square tapered steel pole with base plate "B" type mounting.

### Walkway Lighting Options (final option to be approved by Parks Project Manager):

1. Gardco Gullwing GL13, LED, with round pole adapter on 4 inch diameter straight aluminum pole, 16ft high with black finish. Top of foundation base to be 2 inches above finished grade in lawn areas. Top of foundation to be flush with finished grade if located within finished concrete walkways.

### Site Lighting Options:

1. Optional outlet at base as indicated by Park Project Manager
2. **Optional concrete footing above ground for exterior site lighting in parking lots, 3 foot minimum, as appropriate for site.**

END OF SECTION