

Chapter 9: Automobile and Freight Truck Arterial Networks - 2020

Arterial Streets and Traffic Signals

Arterial streets and traffic signals are available and provide benefit to all users (pedestrian, bicycle, transit, automobile, and freight truck), but previous chapters have discussed pedestrian, bicycle, and transit networks and this chapter focuses on arterial streets and infrastructure as it relates to automobile and freight trucks use. The [Multimodal Transportation Chapter of the Bellingham Comprehensive Plan](#) describes the existing and planned arterial street network needed to support motorized transportation, such as transit busses, private automobiles, and freight trucks. Arterial streets and traffic signal devices are depicted on Figure 8.1.

Major transportation improvements take several years to strategically plan, fund, and construct at great cost. Bellingham adopts a rolling [6-Year Transportation Improvement Program \(TIP\)](#) each June that shows how the City plans to fund and construct major transportation projects.

Bellingham's arterial street network is locally classified into Principle, Secondary, and Collector arterials, with 2017 lane mile totals as follows:

- **Principal Arterial:** Major regional transportation corridors, including State and federal highways, that provide connections into Bellingham from other cities, Whatcom and Skagit Counties, and British Columbia, Canada. Typically very high traffic volumes.
- **Secondary Arterial:** Major local transportation corridors that provide connections across, within, and between different parts of Bellingham. Typically higher to medium traffic volumes.
- **Collector Arterial:** Local transportation corridors that provide connections from neighborhood residential streets to secondary and principal arterial streets. Typically medium to lower traffic volumes.
- **Residential Street:** Local access to individual driveways within residential neighborhoods. Typically lower traffic volumes.

In **2020**, Bellingham's 663-lane mile arterial street network includes the following major features:

Vehicle Lane Miles

- 108 lane miles of principal arterial (16.3%)
- 107 lane miles of secondary arterial (16.1%)
- 61 lane miles of collector arterial (9.2%)
- 387 lane miles of residential streets (58.4%)

Intersection Traffic Control

- 138 intersection traffic signals (+3 in construction; +3 in engineering; +3 in planning study)
- 7 multimodal roundabouts (+1 in engineering; +4 in planning studies)

Person-Activated Crossing Signals

- 28 pedestrian-activated amber flashing crosswalks (+2 in engineering; +2 in planning studies)
- 10 pedestrian hybrid red (HAWK) signals (+2 in planning studies)

Automated Safety Warning Signs

- 47 automated school zone flashing signs
- 2 variable message radar speed signs

Figure 9.1. Bellingham's Arterial Street Network



Designated Freight Truck Network

Bellingham has classified several arterial streets and all state and federal highways as Designated Freight Truck Routes, as depicted below. The City encourages major freight shipping companies to direct their drivers to primarily use the designated freight truck routes, but freight delivery trucks cannot be prevented from using any public street for deliveries unless there are weight restrictions on bridges or other public safety access restrictions. As an example, if a family is moving into or out of a house and has hired a moving company to load or unload their belongings, then the large semi-sized moving van must have access to their house via the local residential street. The same is true for large construction vehicles arriving to residential remodel sites.

In 2015, Bellingham worked with WCOG to collect freight truck counts and update Designated Freight Truck Route classifications by annual freight tonnage according to [WSDOT Freight and Goods Transportation System](#) requirements, as shown below.

Bellingham Designated Freight Truck Route Classifications		
Classification	Annual Tonnage	Example (see map)
T-1	> 10 million	Interstate 5
T-2	4 - 10 million	SR 539 (Guide Meridian)
T-3	300,000 - 4 million	SR 542 (Mt. Baker Highway)
T-4	100,000 - 300,000	12th St-State-Boulevard
T-5	< 100,000	None designated

In 2020, Bellingham is again working with WCOG to collect freight truck counts and update Designated Freight Truck Route classifications by annual freight tonnage. The classifications shown above and on maps in Bellingham transportation planning documents are subject to change based on the findings of these freight traffic counts.

See Chapter 2 discussion of issues emerging in March 2020 as a result COVID-19 global pandemic

Figure 9.2. Bellingham Designated Truck Route Network

