

- 1. BRASS DISK TO BE EQUAL TO OR BETTER THAN SURV-KAP MODEL M/M-B2 (2" DIAMETER WITH ¾" DIAMETER x 2" SHANK).
- 2. EXCAVATION SHALL BE FILLED WITH CLASS 4,000 CONCRETE PER APWA SECTION 03 30 04.
- 3. ALL LOOSE MATERIALS SHALL BE REMOVED FROM THE BOTTOM OF THE HOLE SO THAT THE CONCRETE IS PLACED ON FIRM, UNDISTURBED EARTH.
- 4. THE TOP OF THE CONCRETE SHALL BE TROWELED SMOOTH AND THE BRASS DISK SET IN THE CENTER FLUSH AND LEVEL SO THAT PUNCH MARK FALLS NO CLOSER THAN  $\frac{1}{4}$ " FROM THE EDGE OF DISK.
- 5. EXACT LOCATION OF CONTROL POINT MAY BE PUNCHED AFTER CONCRETE HAS BEEN SECURED IN POSITION.
- 6. DISK SHALL BE STAMPED WITH CITY ASSIGNED MONUMENT NUMBER, SURVEYOR'S LICENSE NUMBER, AND THE YEAR THE MONUMENT IS PUNCHED (YYYY)
- 6. TIE OUT THE MONUMENT USING TRANSIT TIES WITH DISTANCES AND TWO ANGLES. SUBMIT TIE-OUT DOCUMENTATION ON CITY MONUMENT INFORMATION FORM TO CITY PUBLIC WORKS DEPT.
- 7. COMPLETE THE DNR MONUMENT REMOVAL PERMIT PROCESS. (RCW 58.24.040, WAC 332-120)